Additel 920, 920HV Series High Pressure Test Pump

- Generate 95% vacuum to 3,000 psi (200 bar) pressure
- Generate 3,000 psi (200 bar) in 40 seconds
- Minimal maintenance
- Hand-tight quick connectors
- High volume model available



OVERVIEW

The 920 and 920HV High Pressure Test Pump are hand operated pressure pumps designed to generate pressure from 95% vacuum to 3,000 psi (200 bar). With a long lever, it takes just 40 seconds to reach 3,000 psi (200 bar). The high volume (HV) model has been outifitted with a higher volume pump to provide added capacity. A quality screw press is designed for fine pressure adjustment, with an adjustment resolution up to 10 Pa (0.1 mbar).
A specially designed shut-off valve makes the pressure as stable as possible during calibration. A built-in gas-liquid isolator protects the pump from moisture and dirt to reduce the need for maintenance. The residual liquid in the pump introduced from devices under test will be pushed out and collected during pressure release. Two hand-tight quick connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The 920 is an ideal comparison test pump for pressure instruments calibration.

FEATURES

- **High Efficiency**
  Generate 3,000 psi (200 bar) in 40 seconds.
- **Adjustment Resolution**
  0.001 psi (10 Pa, 0.1 mbar).
  High-quality screw press for fine pressure adjustment.
- **Great Stability**
  A specially designed shut-off valve makes the pressure as stable as possible during calibration.
- **Durable and Minimal Maintenance**
  Built-in gas-liquid isolator protects the pump from moisture and dirt.
  The residual liquid in the pump introduced from devices under test will be collected and then pushed out and collected during pressure release.
  Anticorrosive and wear resistant material are used to improve the reliability further.
- **Hand-tight Quick Connectors**
  Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches.

SPECIFICATIONS

- **Media:** Air.
- **Generated Pressure Range**
  95% vacuum to 3,000 psi (200 bar) positive pressure
- **Adjustment Resolution:** 10 Pa (0.1 mbar/0.0015 psi)
- **Material:** Ram/adapters: SS
  Body: SS, aluminum
  Seals: Buna-N, F357, PTFE, Copper Alloy
- **Piston volume:** 60 ml (3.7 in^3) for 920,
  115 ml (7.02 in^3) for 920 HV
- **Connection**
  Hand-tight connectors for both test gauge and reference gauge.
  1/4NPT female, 1/2NPT female, 1/4BSP female, 1/2BSP female, or M20X1.5 female
- **Dimensions:**
  Height: 7.00" (178 mm);
  Base: 21.26' (540 mm) x 10.63" (270 mm).
- **Weight:** 14.3 lb (6.5kg) for 920,
  15.9 lb (7.2kg) for 920HV
- **Warranty:** 1 year

ORDERING INFORMATION

- **Model Number**

ADT920 — N • • SET

Model
ADT920
ADT920HV

Pressure port type:
N -1/4NPT female
N2 - 1/2NPT female
B - 1/4BSP female
B2 - 1/2BSP female
M- M20X1.5 female

SET: Pump and carrying case included

- **Accessories included**
  O-ring: 20 pcs
  Manual: 1 pc
  Carrying case (920-X-SET models only)

- **Optional Accessories**

Model number	*Description*
ADT102	Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs).
ADT103	Adapters and fittings, 1/4NPT (1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs).
ADT100-HTK-8K	Hose test kit, 5 feet flexible hose, 8,000 psi, user selectable male (1/4NPT, 1/2NPT, 1/4BSP, 1/2BSP, M20) to user selectable female hand tight quick connector.
9909-920	Carrying Case for one 920 pump and two 681 gauges or 672 calibrators
9909-920HV	Carrying Case for one 920HV pump and two 681 gauges or 672 calibrators
ADT920-MK	Maintenance kit for Additel 920 pump
ADT920HV-MK	Maintenance kit for Additel 920HV pump

Note: For oil free applications contact Additel.

Phone: 714-998-6899 Fax: 714-998-6999 Email: sales@additel.com
Rev # 20190715

Corporate Headquarters
2900 Saturn St #B
Brea, CA 92821, USA

Salt Lake City Office
1364 West State Rd. Suite 101
Pleasant Grove, UT 84062, USA